



F18 SPRAY GRIGIO

Polyester grey spray filler

A) DESCRIPTION AND FIELDS OF APPLICATION:

Polyester filler for spray application. It hardens quickly even if applied thickly. It fills No. 40 sand scratches and other deep indentations. It can be easily applied also on vertical surfaces.

B) TECHNICAL DATA:

Composition	Polyester resins and mineral charges
Specific weight	1.6 ± 0,1
Available colours	Grey
Safety data	See safety data sheet
	See safety data sheet

C) SURFACE PREPARATION :



* Iron, steel plate, glass reinforced plastic

* Original paints or aged topcoat finishes



* Clean the surface to be treated with V09 Antisil. Make sure it is dry and free from silicone, wax, grease and any extraneous material.

* On base coats or enamel topcoats, sand and clean the surface before spraying.

D) CAUTIONS:

- * Mix well the filler with 5% liquid hardener.
- * Do not utilize the product at temperatures below 10 °C
- * Store in a cool and dry place.



F18 SPRAY GRIGIO

sheet #

F18

E) PROCESSING:



5% liquid hardener Pot life 30' at 20 °C



0-5% D12



**2-2,5 mm 2-4 bar
4-5 = 1000-1200 microns**



**3h at 20 °C
30' at 60 °C**



8-10' at 1 m.



P120-P240

F) TOOLS CLEANING:

* With nitro thinner

G) RECOATING :

**A14, A15 Primer
F09 Fondo Isopol grigio
F04, F16, F02 Fondo Acrilico
F06 Fondo Acrilico Colorabile**

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained