



D11 DILUENTE UNIVERSALE LENTO

Slow thinner for Acrylics

A) DESCRIPTION AND FIELDS OF APPLICATION:

Especially formulated to obtain a great reduction in viscosity. Promotes better flow and prevents blushing, also during hot weather.
Its balanced evaporation insures perfect base and finishing coats.

B) TECHNICAL DATA:

Composition	Ester and ketone base solvents
Specific weight	0,9 ± 0,02
Available colours	Colourless
Safety data	See safety data sheet

C) PROCESSING :

For metalized solvent base coats, 2K acrylic and polyurethane finishes.
For 2K acrylic and polyurethane primer-surfacers.

Mixing ratio : Add from 5% to 100% depending on the required viscosity.

D) CAUTIONS:

* Utilize at above 25°C. temperature.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained

INDUSTRIA CHIMICA REGGIANA - I.C.R. S.p.A

42100 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384 - e-mail: icr@icrsprint.it - www.icrsprint.it

Uff. Comm.le Italia: 42100 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 517803 - Fax +39 0522 231819

International Department: 42100 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 513738 - Fax +39 0522 512446

Stabilimento: 42025 Cavriago - Via Nizzola, 5 - Tel. +39 0522 371818 - Fax +39 0522 575110

Stabilimento: 06074 Perugia - Via Trasimeno Ovest, 159/Z/13 - Tel. +39 075 518611 - Fax +39 075 5186125

CAPITALE SOC. € 557.820,00 - R.E.A. N. 82109 M. R.E. 000534 - Reg. Imprese, COD. FISC. e PART. IVA 00140910357